

Terminal Tractor/Yard Spotter

Used Yard Spotter Rialto - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. They are capable of towing several trailers in a train formation. Some are designed specifically to tow large aircraft in order to position them into and out of airport terminals and hangers. The tractive effort concept is how loads move from place to place. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. Heavier loads require more tractive effort compared to lighter loads. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The hydraulic mast on the tow tractor is responsible for lifting the load. It produces downforce on the drive wheel underneath to increase the tractive effort. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides. Types of Tow Tractors Heavy-duty tow tractors and load carriers are two types of tow tractors. Load Carriers Industries such as e-commerce, manufacturing, and airport baggage and parcel systems must regularly move many individual and varying sized items to or from a single location. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. Load carrier tow tractor models are categorized in the material handling equipment that covers cranes, forklifts and pallet jacks. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. This means that the load has already been on wheels or placed on a wheeled platform before transport. Wheeled platforms are called skates, trollies and bogies. The tow tug is attached to the trolley similar to train cars being attached to a locomotive. Typically, the tow tug features a steel coupling male-end that attaches to a female-end on the trolley's front. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. Tow tractors are capable of moving many machines in a variety of conditions. The availability of many different types of trollies also allows for greater customization in transporting items. Many trollies can be connected since they are compatible with one another. Different kinds of trollies can be maneuvered in a single train, creating flexible transport options. An additional benefit of operating with load carrier tow tractors as opposed to forklifts is the unobstructed view offered by a tow tractor, increasing the safety of work areas. Load carrier tow tractors transport trollies in a forward direction which decreases the safety concerns common with reverse forklift operations. This design is excellent for locations that have a high level of safety such as manufacturing locations and airports. Towing solutions are a good alternative to traditional forklifts to handle many single items. They are safe and easy to maneuver. One benefit of these tow tugs is that an operator usually does not require a license. This is because the load is not lifted from the ground so it does not fall under the usual restrictions and licensing required of standard forklifts, cranes and other load lifting equipment. Three subtypes of load carrier tow tractors include rider-seated, stand-in and pedestrian. Pedestrian Tow Tractors A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. These machines are simple to use, extremely maneuverable and very compact. Stand-in Tow Tractors Popular for industries that conduct order picking and horizontal transport for manufacturing, the stand-in tow tractors are the best design. These units deliver a secure driver platform and deliver a smaller footprint compared to the rider-seated models. Rider-Seated Tow Tractors The rider-seated tow tractors are similar to the stand-in tow tractors with the exception they provide a seated platform for the driver. These models are commonly used for transporting loads over farther distances such as moving checked baggage from the airport check-in to the aircraft at the terminal. Rider fatigue is decreased with sit-down units for more efficiency and productivity. Heavy Duty Tow Tractors In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. This pushback process is

done by using specially designed heavy duty tow tractors called pushback tractors or pushback tugs. Pushback tractors are built with a low-profile to allow them to move underneath the nose of the aircraft so that it can attach. Since the aircraft weight is heavy, these units need to be heavy in order to retain adequate ground friction to move the aircraft. Large aircraft tractors can weigh as much as fifty-four tons. These models have a driver's cab that has the option of being raised or lowered during reverse for better visibility. While the vehicle is referred to as a pushback tug or pushback tow tractor, it is also used to tow aircraft in areas where taxiing the aircraft is not practical or safe, such as moving large aircraft in and out of maintenance hangars. There are two subtypes of pushback tow tractors: 1. Conventional; and 2. Towbarless. Conventional Pushback Tow Tractors Conventional tugs use a tow bar to connect the tug to the nose landing gear of the aircraft. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. The tow bar that attaches to the tug can pivot vertically and laterally. The tow bar functions as a sizeable lever to facilitate nose landing gear rotation. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor. Towbarless Pushback Tow Tractors Towbarless tractors work without a towbar and scoop up the aircrafts' nose landing gear to lift it off of the ground instead. This allows better control of the aircraft and higher speeds; it may also eliminate the need to have a worker in the cockpit to apply the aircraft's brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.